

REBEL™ SELF RETRACTING LIFELINES



**TOTAL
COMPLIANCE.
ABSOLUTE
CONFIDENCE.**

TRUSTED, QUALITY FALL PROTECTION



DEPENDABILITY

YOU CAN RELY ON EVERY DAY

Protecta® continues to set the standard for performance and value.

The Rebel™ Self Retracting Lifeline (SRL) range is built to last providing an economical fall protection solution without compromising performance or safety!

Markets Served

- Commercial Construction
- Residential Construction
- Industrial Maintenance
- Roofing Applications
- Mining & Resources
- And More!

Durable

- Built to last
- Heavy-duty Thermoplastic housing
- Stackable housing design

Reliable

- 140kg capacity
- Side cable exit
- Top and bottom swivel connections
- Fall indicator hook
- Heavy duty 16kN gate capacity

Sharp edge compliant

- Meets the CE sharp edge certification requirements for horizontal use when used with an SRL shock absorbing unit (Part No. Z6)

Easy to maintain

- The design of the Rebel is made up of 30% less parts than other SRL's
- Several parts are common to different model sizes making periodic servicing quicker and easier



Rebel Compact SRL Range

Available in both webbing and cable variants

Top Swivel
Limits lifeline twisting

Rugged Aluminium Housing
Provides exceptional strength and durability

Side Webbing/Cable Exit
Enables smooth operation and reduces cable wear

High Strength Thin Webbing or Galvanised Cable for Hot Work
For added durability and longevity

Impact Indicator
Provides visual indication of fall arrest, available on selected models

16kN Gate Capacity
Reduces chance of accidental disengagement ("roll-out")

Self Locking Snap Hook
Automatically closes and locks for added safety
Models with triple action karabiners also available



EXPLORE THE SYSTEM



1 Top Swivel
Limits lifeline twisting

2 140kg Capacity
Higher capacity for operator and tools

3 Ergonomic Carrying Handle
Built-in design makes transport, set-up and storage easy

13 Thermoplastic Housing
Lightweight, compact and durable

12 Aluminium Housing
Provides exceptional strength and durability

11 Stackable
Housing design allows for stacking on work surfaces

4 Ergonomic Cable Handle
Provides added comfort and ease-of-use when making connections

5 Swivel Hook
Limits lifeline twisting

6 Impact Indicator
Provides visual indication of fall arrest

10 Side Cable Exit
Enables smooth operation and reduces cable wear

9 Galvanised and SS Cable
Stainless steel option for added corrosion resistance

8 Self Locking Snap Hook
Automatically closes and locks for added safety
Models with triple action karabiners also available

7 16kN Gate Capacity
Reduces chance of accidental disengagement ("roll-out")



All Rebel Self Retracting Lifelines come complete with connecting karabiners on housing

All Rebel SRL Mining Specific models feature triple action karabiners on anchorage and lifeline connectors

BONUS
First Service included
FREE with every
6, 10, 15, 20, and 30 metre
Rebel Self Retracting Lifelines
Not applicable to rebel compact range, see terms & conditions on reverse.

	Compact			New				
	3.3m	4.5m	6.0m	6.0m	10m	15m	20m	30m
1 Swiveling Anchorage Connection	✓	✓	✓	✓	✓	✓	✓	✓
2 140kg Capacity				✓	✓	✓	✓	✓
3 Carrying Handle				✓	✓	✓	✓	✓
4 Cable Handle				✓	✓	✓	✓	✓
5 Swiveling Hook		✓	✓	✓	✓	✓	✓	✓
6 Impact Indicator		✓	✓	✓	✓	✓	✓	✓
7 16kN Rated Gate	✓	✓	✓	✓	✓	✓	✓	✓
8 Self Locking Snap Hook	✓	✓	✓	✓	✓	✓	✓	✓
9 5mm Wire Rope (Gal or SS)		✓		✓	✓	✓	✓	✓
10 Side Cable/Webbing Exit	✓	✓	✓	✓	✓	✓	✓	✓
11 Stackable				✓	✓	✓	✓	✓
12 Aluminium Housing	✓	✓	✓	✓	✓	✓	✓	✓
13 Thermoplastic Housing				✓	✓	✓	✓	✓
14 High Strength Thin Webbing	✓		✓					
Bonus Servicing Voucher				✓	✓	✓	✓	✓

SELECTION GUIDE / SPECIFICATIONS

Cable/Web Length		3.3m	3.3m	4.5m	6.0m	6.0m	10m	15m	20m	30m
Lifeline Material	Thermoplastic Housing									
	Aluminium Housing									
	Swiveling Anchorage									
	Swiveling Hook									
	Triple Action Karabiners (Mine Spec)									
	140kg Weight Capacity									
Gal Cable	•					3590520	3590521	3590570	3590610	3590690
	•						3590506		3590595	3590675
	•					3590530	3590531	3590580	3590620	3590700
	•			3506055						
SS Cable	•						3590522	3590571	3590611	3590691
	•						3590532	3590581	3590621	3590701
Web	•	AD111ARA								
	•		AD111R-45-45							
	•				AD120BR					
Weight		1.75kg	1.75k	3.80kg	2.70kg	Thermoplastic 5.5kg	Thermoplastic 5.8kg	Thermoplastic 7.7kg	Thermoplastic 10.2kg	Thermoplastic 13.6kg
						Aluminium 6.9kg	Aluminium 7.2kg	Aluminium 9.3kg	Aluminium 12.6kg	Aluminium 16.0kg
Approximate Depth		5cm	5cm	5.5cm	5.5cm	12cm	12cm	12cm	14cm	14cm
Approximate Width		10cm	10cm	14cm	14cm	25cm	25cm	28cm	33cm	33cm
Approximate Height (anchor point to anchor point, incl. top karabiner)		57cm	55cm	72cm	64cm	65cm	65cm	69cm	73cm	73cm
Karabiners		Double action: 19mm gate opening, 16kN gate, 23kN body, alloy steel (anchorage connector on all Rebel models except mine specific models) Triple action with captive eye: 22mm gate opening, 16kN gate, 41kN body, stainless steel (anchorage & lifeline connector on Compact Rebel mine specific model) Triple action with captive eye: 50mm gate opening, 16kN gate, 22kN body, high tensile steel (anchorage connector on Newly Designed Rebel mine specific models) Triple action with captive eye, swivel & fall indicator: 20mm gate opening, 16kN gate, 22kN body, high tensile steel (lifeline connector on Newly Designed Rebel mine specific models)								
Snap Hooks		Double action (non swivel) - 19mm gate opening, 16kN gate, 23kN body, alloy steel (lifeline connector on AD111ARA Compact Rebel model) Double action with swivel & fall indicator - 19mm gate opening, 16kN gate, 23kN body, alloy steel (lifeline connector on all Rebel models except AD111ARA and mine specific models)								
Maximum Arresting Force/Distance		Maximum Arresting Force = 6kN Maximum Arresting Distance = 0.6m								
Standards		Meets EN 360 and AS/NZS 1891.3								
Compatibility		Rebel SRL's are compatible for use with all Capital Safety approved components and systems, or as recommended by a competent person								
Country of Origin		U.S.A.								
Special Instructions/Conditions of Use		Reading User Instruction Manual prior to use is essential								

Model numbers highlighted in **YELLOW** are Velocity Ship lines, velocity Ship lines are available for same day despatch, all other models are non-stocked items and require longer lead times.

Bonus Servicing Offer

Capital Safety will provide a Servicing Voucher with every applicable Rebel Self Retracting Lifeline that is valid for the lifelines first standard service. Self Retracting Lifelines are life saving devices, Capital Safety recommends that all Self Retracting Lifelines be serviced annually and where used in harsh conditions, more frequent inspection may be required.

NOTE: Inspection and servicing requirements must be followed in accordance with the standard or the manufacturer's user instructions.

Terms & Conditions

- Free First Service Covers: consumable parts used in annual servicing, labour, final inspection and certification.
- Free Service does not cover: freight, damaged components during normal/excessive use such as housings, cable, hooks, etc., cleaning due to contamination, corrosion or similar.
- Bonus Servicing Offer applicable to the NEW 6, 10, 15, 20, and 30 metre Rebel Self Retracting Lifelines only (Part no's: 3590506, 3590520, 3590521, 3590522, 3590530, 3590531, 3590532, 3590570, 3590571, 3590580, 3590581, 3590595, 3590610, 3590611, 3590620, 3590621, 3590675, 3590690, 3590691, 3590700, 3590701).
- Bonus Servicing Offer **NOT** applicable to the Rebel Compact range.



Contact Capital Safety for more information on Protecta's range of Rebel Self Retracting Lifelines, or visit www.rebel.capitalsafety.com.au.

Alternatively scan the QR Code above with your smart phones QR scanner/reader. QR readers are available for free from your mobiles app store.



Capital Safety - Australia & New Zealand
Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

- Asia: +65 6558 7758
- Latin America: +1 651 385 4301
- USA: 800.328.6146
- Northern Europe: +44 (0) 1928 571234
- Canada: 800 387 7484
- Germany: +49 2634 8052
- Europe, Middle East, Africa: +33 (0)4 97 10 00 10

